SERVICE STATION OCCUPANCIES

The B.C. Fire Code requires building owners/occupants to comply with the requirements on this checklist

These requirements are in addition to those listed in the Fire Safety & You booklet.

Service Station uses Include: Gas/fuel filling stations & automotive shops

U	,
Checklist: Common Fire Service Requirements	
 ☐ Address: must be visible from road and lane, free from foliage, trees, etc. and in a contrasting colour. ☐ Attendants: must be trained as per BC Fire 	 'No smoking, engine off' signs: must be posted at dispensing equipment. Portable fire extinguishers must: be located adjacent to corridors or aisles that
Code 4.6.8.5. and 4.6.8.6. Cutting/welding equipment: compressed gas	provide access to exits.
☐ Cutting/welding equipment: compressed gas bottles must be secured and have check valves. There must be no mechanical damage to gas hoses.	 be mounted in a visible location, accessible, and serviced and tagged at least once every 12 months by a certified technician.
Dispensing hose: check for physical/ mechanical damage.	 be full and functioning (no damage, corrosion, leaks, malfunctioning parts or clogged nozzles.)
☐ Dispensing unit shut-off devices: must be clearly identified, remote and shielded from fire. At marine service stations, they must have a readily accessible valve in each pipeline at or within 7.5 metres of pier to shut off supply from shore.	 have a minimum rating 2A-10BC.
	□ Propane cylinders: cylinders inside must be connected to appliance/equipment and all cylinders (full or empty) must be stored outside in a secure location.
☐ Electrical equipment: no extension cords permitted	☐ Propane fueling: no combustibles may be stored near tanks.
☐ Fire doors: must not be blocked or wedged open, including stairwell doors. Must have closures and no wedges to hold open fire rated doors.	☐ Soiled rags: must be disposed of in an approved metal container with a tight-fitting lid.
	☐ Tire storage : area must be 10 feet from building, neat and orderly. Large quantity of storage not permitted. (100 metres sq.)
Fire separations: must have no holes or openings that compromise their purpose.	☐ Wash tanks: it is recommended that wash tanks
☐ Garbage disposal: commercial containers	
must be located three metres from combustible buildings. If inside, commercial containers should have tight-fitting lids and be in fire-separated rooms.	☐ Waste oil storage: maximum storage permitted in an above-ground storage tank is 5,000 litres.
☐ Heating units: check condition of units. No	



portable heaters permitted.

