



**NOTES:**

1. TEMPORARY PATCH MUST BE MAINTAINED FOR A MINIMUM 3 MONTHS TO ALLOW FOR SETTLEMENT OF TRENCH OR AS DIRECTED BY ENGINEER
2. TEMPORARY ASPHALT SURFACE MUST BE RESTORED TO SMOOTH CONDITION AND MATCH WITH GRADE OF ADJACENT PAVEMENT
3. DEVELOPER REQUIRED TO EFFECT REPAIRS TO TEMPORARY PAVEMENT RESTORATIONS WITHIN 7 DAYS FROM WRITTEN RECEIPT OF NOTICE FROM THE ENGINEER OR IMMEDIATELY IF THE ENGINEER CONSIDERS THE TEMPORARY PATCH TO BE A SAFETY RISK.
4. TEMPORARY PAVEMENT RESTORATIONS OPEN TO TRAFFIC MUST BE RESTORED WITH DEFLECTION TOLERANCES OF NOT MORE THAN 25mm UP OR DOWN, MEASURED WITH A 1m STRAIGHT EDGE
5. IF THE DEVELOPER FAILS TO MAINTAIN THE TEMPORARY ASPHALT RESTORATION TO THE ABOVE SPECIFICATIONS, THE CITY WILL REPAIR AT THE COST OF THE DEVELOPER.
6. REFER TO CS-R-16 FOR PERMANENT TRENCH PAVEMENT RESTORATION REQUIREMENTS

**TEMPORARY UTILITY TRENCH  
PAVEMENT RESTORATION  
(LONGITUDINAL OR TRANSVERSE)  
(UNDER REVIEW)**



DRAWN: 1997 01 27

REVISED: 2014 10 30

APPROVED BY:

**CS - R - 9**