



NOTES:

1. PURPOSE IS TO PROTECT HILLSIDE FROM EROSION BY CONVEYING RUNOFF TO AN APPROVED LOCATION.
2. TIRES, SANDBAGS, OR EQUIVALENT MAY BE USED TO WEIGHT PLASTIC SHEETING.
3. SEAMS BETWEEN SHEETS MUST OVERLAP A MINIMUM OF 1M AND BE WEIGHTED OR TAPED.
4. PLASTIC SHEETING SHALL HAVE A MINIMUM THICKNESS OF 6 MIL.
5. DUE TO RAPID RUNOFF CAUSED BY PLASTIC SHEETING, THIS METHOD SHALL NOT BE USED UPSLOPE OF AREAS THAT MIGHT BE ADVERSELY IMPACTED BY CONCENTRATED RUNOFF.
6. CONSTRUCT BERM OR SWALE AT TOP OF SLOPE TO CONVEY UPSLOPE WATER TO A STABILIZED POINT OF CONVEYANCE (I.E. TEMPORARY SLOPE DRAIN).
7. CONSTRUCT DITCH AT BASE OF SLOPE FOR DISCHARGE TO APPROVED LOCATION.
8. AN ALTERNATIVE TO PLASTIC COVERS ARE ROLLED EROSION CONTROL PRODUCTS.

**TARP/PLASTIC COVERING  
FOR SLOPES & STOCKPILES**



DRAWN: 2002 05 31  
 REVISED: 2010 07 26  
 APPROVED BY:

ES - EC - 11