ASSEMBLY OCCUPANCIES

The B.C. Fire Code requires building owners/occupants to comply with the requirements on this checklist.

These requirements are in addition to those listed in the Fire Safety & You booklet.

Assembly uses Include: Places used for gatherings such as; places of worship, nightclubs/ pubs, community halls, libraries, and restaurants.

Checklist: Common Fire Service Requirements

- Address: must be visible from road and lane, free from foliage, trees, etc. and in a contrasting colour.
- Aisleways: must provide a clear access to exits.
- Decorations: must be non-combustible or treated.
- **Drapes:** must be treated.
- □ Emergency lighting: may be provided by battery packs with remote and attached heads, or by emergency generators that will illuminate specified A/C fixtures or remote light heads. Must be operational, with no visible damage, and serviced and tagged annually by a certified technician.
- Exit doors: must not be locked or blocked from either the inside or outside. Must be unlocked from the inside when the building is occupied. Must have panic hardware that releases when a force of 20 pounds or less is applied.

Exit signs: must be visible and remain illuminated at all times the building is occupied.

- Extension cords: kept to a minimum and not overloaded.
- □ **Fire alarm systems:** must have a working A/C power-on bulb and be in good working condition with no audible or visual damage. Must have a current service tag (within the last 12 months) and up-to-date logbook.
- □ **Fire doors**: must not be blocked or wedged open, including stairwell doors. Must have

closures and no wedges to hold open fire rated doors.

- Fire Safety Plan: Must be reviewed and revised yearly.
- ☐ **Fire hydrants**: must be accessible, free of damage and serviced within the specified date. Private hydrants require annual service, with records kept on site.
- **Fire separations**: must have no holes or openings that compromise their purpose.
- ☐ Garbage disposal: commercial containers must be located three metres from combustible buildings. If inside, commercial containers should have tight- fitting lids and be in fireseparated rooms.
- □ Occupant load: Submit occupant load calculation per B.C. Fire Code requirements to Fire Prevention Branch Office for review.
- □ Portable fire extinguishers must:
 - be located adjacent to corridors or aisles that provide access to exits.
 - be mounted in a visible location, accessible, and serviced and tagged at least once every 12 months by a certified technician.
 - be full and functioning (no damage, corrosion, leaks, malfunctioning parts or clogged nozzles.)
 - have a minimum rating 2A-10BC.
- **Portable heaters:** must be an approved type and kept away from combustibles.



